



UG6KB05 THRU UG6KB100


SINGLE PHASE 6.0AMP GLASS PASSIVATED BRIDGE RECTIFIER

Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Designed for surface mount application
- Plastic material-UL flammability 94V-0

Mechanical Data

- Case: D3K, molded plastic
- Terminal: Plated leads solderable per MIL-STD 202, Method 208
- Polarity: As Marked on case
- Mounting Position: Any
- Marking: Type Number
- Lead Free: For RoHS/Lead Free Version



Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.
Single Phase, half wave, 60Hz, resistive or inductive load.
For capacitive load, derate current by 20%.

TYPE NUMBER	SYMBOL	UG6K B05	UG6K B10	UG6K B20	UG6K B40	UG6K B60	UG6K B80	UG6K B100	UNIT	
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM}								V	
	V_{RWM}	50	100	200	400	600	800	1000		
	V_{DC}									
RMS Reverse Voltage	V_{RMS}	35	70	140	280	420	560	700	V	
Average Rectified Output Current	$I_F(AV)$	Without heat sink @ $T_c=90^\circ C$				3.0				A
		With heat sink @ $T_c=90^\circ C$				6.0				
Non-Repetitive Peak Forward Surge Current 8.3ms Single half sine-wave superimposed on rated load (JEDEC Method)	I_{FSM}					150				A
I^2t Rating for Fusing ($t < 8.3ms$)	I^2t					93.375				A^2s
Forward Voltage per element @ $I_F=6.0A$	V_{FM}					1.1				V
Maximum DC reverse current at $T_J=25^\circ C$ rated DC blocking voltage per leg $T_J=125^\circ C$	I_R					5.0 200				μA
Dielectric Strength	V_{ids}					2500				V
The proposed installation torque Max torque	T_{or}					5.0 8.0				Kgf.cm
Typical Junction Capacitance (Note 1)	C_J					45				pF
Typical thermal resistance	$R_{\theta JA}$					55				$^\circ C/W$
	$R_{\theta JL}$					15				
Operating and Storage Temperature Range	T_J, T_{STG}					-55 to +150				$^\circ C$

Note: 1. Measured at 1.0 MHZ and applied reverse voltage of 4.0VD.C.



UG6KB05 THRU UG6KB100

Fig. 1 Output Current Derating Curve




Fig. 2 Typical Forward Characteristics




Fig. 3 Maximum Peak Forward Surge Current




Fig. 4 Typical Junction Capacitance Per Diode





Fig. 5 Typical Reverse Characteristics (per element)





UG6KB05 THRU UG6KB100

Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from XINNUO
- XINNUO reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.
XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.