



# GBU35005A THRU GBU3510A


SINGLE PHASE 35.0 AMP GLASS PASSIVATED BRIDGE RECTIFIER

## Features

- Glass passivated die construction
- Low forward voltage drop
- High current capability
- High surge current capability
- Plastic material-UL flammability 94V-0

## Mechanical Data

- Case: GBU, molded plastic
- Terminals: Plated Leads Solderable per MIL-STD-202, Method 208
- Polarity: As Marked on Case
- Mounting Position: Any
- Marking: Type Number
- Lead Free: For RoHS / Lead Free Version



dimensions in inches and (millimeters)

## Maximum Ratings and Electrical Characteristics

Rating at 25°C ambient temperature unless otherwise specified.

Single Phase, half wave, 60Hz, resistive or inductive load.

For capacitive load, derate current by 20%.





TYPE NUMBER	SYMBOL	GBU 35005A	GBU 3501A	GBU 3502A	GBU 3504A	GBU 3506A	GBU 3508A	GBU 3510A	UNITS
Peak Repetitive Reverse Voltage	$V_{RRM}$								
Working Peak Reverse Voltage	$V_{RWM}$	50	100	200	400	600	800	1000	V
DC Blocking Voltage	$V_{DC}$								
RMS Reverse Voltage	$V_{RMS}$	35	70	140	280	420	560	700	V
Average Rectified Output Current (with heatsink) @ $T_c=90^\circ\text{C}$ (without heatsink)	$I_{F(AV)}$				35 3.6				A
Non-Repetitive Peak Forward Surge Current @ $T_j=25^\circ\text{C}$ 8.3ms Single half sine-wave superimposed @ $T_j=125^\circ\text{C}$ on rated load (JEDEC Method)	$I_{FSM}$				350 280				A
Non-Repetitive Peak Forward Surge Current 1 ms Single half sine-wave superimpose on rated load (JEDEC Method)	$I_{FSM}$				700 560				A
Forward Voltage per element @ $I_F=17.5\text{A}$	$V_{FM}$				1.1				V
Peak Reverse Current @ $T_A=25^\circ\text{C}$ At Rated DC Blocking Voltage @ $T_A=125^\circ\text{C}$	$I_R$				5.0 200				$\mu\text{A}$
$I^2t$ Rating for fusing ( $t < 8.3\text{ms}$ )	$I^2t$				508.375				$\text{A}^2\text{s}$
Typical Junction Capacitance per leg (Note 2)	$C_J$				110				pF
Typical Thermal Resistance per leg (Note 3)	$R_{\theta JC}$				1.6				$^\circ\text{C}/\text{W}$
(Note 4)	$R_{\theta JL}$				1.0				
Operating and Storage Temperature Range	$T_J, T_{STG}$				-55to+150				$^\circ\text{C}$

Note:

1. Measured at 1.0 MHz and applied reverse voltage of 4.0V D.C.
2. Thermal Resistance Junction to Case, device mounted on heatsink
3. Thermal Resistance Junction to Lead, device mounted on heatsink



# GBU35005A THRU GBU3510A





## Important Notice and Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from XINNUO
- XINNUO reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.
- XINNUO disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- XINNUO does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the here in document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications.  
XINNUO makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown here in are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify XINNUO for any damages resulting from such improper use or sale.
- Since XINNUO uses lot number as the tracking base, please provide the lot number for tracking when complaining.